

CORNERS: DOUBLE STEEL PIPE POST WITH
CABLES TERMINATING

NOTE: DETAIL IS TYPICAL FOR 1/8", 3/16" AND 1/4" DIAMETER CABLERAIL KITS

1-7/8" O.D. x 1-1/2" I.D. MIN. EXTRA
STRONG STEEL PIPE OR OTHER TYPE
AND SIZE RECOMMENDED BY
MANUFACTURER OR ENGINEER.

DRILL HOLE THROUGH PIPE.
CONFIRM DRILL DIAMETER WITH
MANUFACTURER.

∅ CABLE

STAINLESS STEEL
QUICK-CONNECT[®] INSET

END FITTINGS:
END CAP, COLORED POLYETHYLENE (STANDARD)
OR ST. STL. (OPTIONAL)
3/4" O.D. NYLON FLAT WASHER

END FITTINGS:
END CAP, COLORED POLYETHYLENE (STANDARD)
OR ST. STL. (OPTIONAL)
ST. STL. SNUG-GRIP[®] WASHER-NUT (COVERED)
3/4" O.D. NYLON FLAT WASHER

DECK BELOW

STAINLESS STEEL
THREADED TERMINAL

DRILL HOLE THROUGH PIPE.
CONFIRM DRILL DIAMETER
WITH MANUFACTURER.

∅ CABLE

CableRail Reference Drawing:
TERMINATIONS IN DOUBLE CORNER STEEL TUBES POSTS

THIS DRAWING IS THE PROPERTY OF FEENEY INC. ANY REPRODUCTION OF THIS DOCUMENT WITHOUT THE EXPRESSED WRITTEN CONSENT OF FEENEY INC. IS STRICTLY PROHIBITED.

DATE:	05/15/13
PAGE:	1 of 1
REV:	A - 12/06/17 (MRJ)
BY:	DSY
CHK:	BWA



2603 Union St., Oakland, CA 94607
P: 800-888-2418 F: 510-893-9484
www.feeneyinc.com