

CableRail


Quick-Connect® Internal Thread Adjuster

Feeney® Quick-Connect® Internal Thread Adjusters can be used when there is access to the outside post face. The Internal Thread Adjuster fits into a hole drilled in end post. Internal Thread Adjusters can be used in level or stair applications. Use with Feeney Bulk Cable, sold separately.

FEATURES & BENEFITS

- For use with wood or metal frames, level or stair railings
- Made of Type 316 marine-grade stainless steel
- Inserts through a drill hole in the post and is secured and adjusted with a square drive bolt and washer (included) - #9807 has 3/16-in hex head bolt
- Use beveled washers for angled stair terminations and flat washers for added bearing surface on wood posts
- Typically paired with Internal Thread Adjuster but can be paired another Tension Adjustment fitting for one run of cable







OUICK-CONNECT® INTERNAL THREAD ADJUSTER

Part#	CableØ	Thread	ВØ	WØ	L closed (open)	QCØ	DrillØ
9907-PKG	1/8"	1/4-20	7/16"	11/16"	2-3/4" (3-1/2")	7/16"	*5/16"
9908-PKG	1/8"	1/4-20	7/16"	11/16"	3-1/4" (4")	7/16"	*5/16"
9909-PKG	1/8"	1/4-20	7/16"	11/16"	4-1/4" (5")	7/16"	*5/16"
9807	3/16"	5/16-18	1/2"	3/4"	3-1/4" (4")	9/16"	*3/8"

*DrillØ is clearance hole for threaded bolt shaft only. To embed the QC body into the post, drill a hole slightly larger than the QC Ø.

FEENEY IS A MEMBER OF:















QUICK-CONNECT® TECHNOLOGY



Feeney Quick-Connect® fittings offer the flexibility of assembling cables in the field with simplicity and speed. Patented automatic-locking-jaws grip the cable with no need for specialized tools. Simply trim your cable to length, push the end into the Quick-Connect® fitting, and the spring-loaded jaws automatically engage. You're ready to go!

Made from 316-grade stainless steel for weather-tough durability, low maintenance, and lasting beauty. Fittings also come with a silicone protection seal pre-inserted into the end, providing added protection against dirt and debris entering the body of the fitting. If necessary, our Quick-Connect® Release Tool can be used to disengage and remove or readjust the fitting.



There are two types of fittings: Fixed End fittings and Tension Adjustment fittings.

Each cable run must include at least one Tension Adjustment fitting.

TENSION ADJUSTMENT FITTINGS

- Include Tensioner fittings, Turnbuckles, Threaded Terminals, and Adjusters
- Tension is adjusted by spinning the tubular body on Tensioners and Turnbuckles, tighting the bolt on ThreadedTerminals, or rotating the bolt on the Adjusters
- Tension Adjustment fittings can be paired with either a Fixed End or another Tension Adjustment fitting.

FIXED END FITTINGS

- Non-adjustable end termination fittings
- No tensioning capabilities
- Must be paired with a Tension Adjustment fitting

NOTE:

CableRail is made of marine grade stainless steel and will last for years with regular maintenance. Learn more: feeneyinc.com/Warranty-and-Care.

EASY INSTALLATION



TRIM CABLE TO LENGTH



INSERT CABLE INTO FITTING



JAWS LOCK AUTOMATICALLY

SPECIALLY ENGINEERED TOOLS FOR CABLERAIL



Quick-Connect® Release Tool

For releasing the Quick-Connect® jaws to remove or adjust fitting.



Wrench Wheel

An easy-to-use tool for tensioning Quick-Connect® Tensioner fittings.



Cable Lacing Needle

For quickly lacing cable ends through posts without snagging.



Cable Tension Guage

Easy-to-use tool for checking cable tension.



Stainless Steel Cleaner Kit

Clean and maintain all stainless steel surfaces, fittings, and cables.